Price List 01-01-2025 SCANER Microscopes

| W) so | CANER | Pro 11.600 € | Master 13.600 € | Excellent 15.900 € | Fluorescence 17.400 € |
|---|--|--------------------|--------------------|-----------------------|--------------------------|
| Code | Mount s | ystems | | | |
| 61600 | Floor stand | ✓ | 1 | 1 | 1 |
| 64600 | Ceiling mount (ceiling height not more than 3,7 m) | - 140* | - 140* | - 140* | - 140* |
| 62700 | Wall mount | - 190* | - 190* | - 190* | - 190* |
| | Binocular tuk | pes | | | |
| 50600 | Binocular tube with 0° ocular tilt angle | - | - | - | |
| 20700 | Binocular tube with 45° ocular tilt angle | ✓ | - | - | |
| 60800 | Binocular tube with variable ±90° ocular tilt angle | + 1 320 | ✓ | 1 | 1 |
| | Objective lens | ses | 1 | T | |
| 64200 | Objective lens f=200 mm with fine focusing | 0* | - | - | |
| 64210 | Objective lens f=250 mm with fine focusing | 1 | ✓ | - | |
| 64220 | Objective lens f=300 mm with fine focusing | 0* | - | - | |
| 64230 | Objective lens f=350 mm with fine focusing | 0* | - | - | |
| 64240 | Objective lens f=400 mm with fine focusing | 0* | - | - | |
| 52800B02 | Variable objective lens f=200-400 mm with protective glass | + 1 980 | + 1 980 | ✓ | ✓ |
| | Characteristics and functions | of the optical hea | ad | | |
| Optical magnification for f 250 mm - 3X, 5X, 9X, 14X, 22X | | 1 | 1 | 1 | ✓ |
| Passive cooled LED Illuminator 115 000 lux at f=250 mm, 5700k, CRI-94, R8 = 80 | | 1 | 1 | 1 | ✓ |
| | Knob for adjusting the light on the optical head of the microscope and turning on the mode «Smart Light» | | 1 | 1 | 1 |
| Orange and gre | Orange and green filters | | ✓ | 1 | ✓ |
| | «Smart Light» - system of automatic regulation of illumination while changing magnification | | + 320 | ✓ | 1 |
| «Fluorescent Light» - fluorescent backlight mode + filter input system to protect the eyes and increase the contrast of the fluorescent image dimming | | + 1 500 | + 1 500 | + 1 500 | 1 |
| | Optical adapter for photo a | | | | |
| 52100B | 60° binocular adapter with one 20/80 optical channel divisor | +680* | ✓ | ✓ | ✓ |
| 63902A | 0° binocular adapter with one 20/80 optical channel divisor | ✓ | - | - | |
| 62200 | Adapter for connecting cameras Sony™, | + 1 580 | + 1 580 | + 1 580 | + 1 580 |
| 64100 | Adapter 3D to connect smartphone (with Android/IOS application "SOVA") | + 1 690 | + 1 690 | + 1 690 | + 1 690 |
| 64900A | Adapter for GoPro (with GoPro hero 12 black) | + 2 890 | + 2 890 | + 2 890 | + 2 890 |
| U43UUA | black) | + ∠ 090 | + 2 890 | + 2 890 | + 2 890 |

| Additional accessories | | | | | | |
|--|-----------------------------------|----------|----------|----------|-------|--|
| 52800B02 | Protective glass | + 280 | + 280 | ✓ | ✓ | |
| 54000.01 | Monitor mount | + 260 | + 260 | + 260 | + 260 | |
| 54000.02 | Tablet mount with power supply 5v | + 580 | + 580 | + 580 | + 580 | |
| 54900.03 | Set of silicone caps | ✓ | < | √ | ✓ | |
| Additional functions | | | | | | |
| Automatic switching off the light at raising of an optical head up into a non-working zone | | ✓ | ✓ | √ | ✓ | |
| 2 USB ports with power supply 12V on the optical head bracket for powering photo and video accessories | | ~ | * | ✓ | ✓ | |
| Special monitor indication of the current magnification values, "Smart Light", "Fluorescent Light" switching-on modes and the current temperature of the LED | | ✓ | ~ | ✓ | • | |
| Protection system of the power supply unit and the balancing lever against damages during their folding | | ✓ | ✓ | √ | ✓ | |
| IP64 waterproof and dust ingress of the illuminator and the optical head | | ✓ | ✓ | 1 | 1 | |

^{*} The difference in price between the standard option and the selected one

SCANER products meet the requirements of the European directive MDD 93/42 / EEC

SCANER is certified according to the requirements of the international standard ISO 13485: 2016

3 years warranty from supplier SCANER

All prices quoted are excluding VAT.